



## Product Model Stud End Fixing

For anchoring into concrete ceilings, metal decking and pressed metals.

<b>Safe Working Load</b>	Up to 225 kg Use with a No.1, No.2, No.3 or No.4 Gripple hanger
<b>Material</b>	Steel Finish - BZP

### Installation

1. Drill concrete (Use wire brush to ensure the hole is clear)
2. Push in the Drop-in anchor
3. Use a hammer to drive in the setting punch to expand the anchor
4. Screw in the stud

Technical data  
supplied by the  
manufacturer



### Important Information

1. Construction materials and conditions vary on different sites. If it is suspected that the base material has insufficient strength to achieve a suitable fixing, contact Gripple Ltd. The responsibility for judgement of base material strength lies with the installer, and not with Gripple Ltd.
2. Not to be used in marine, coastal or corrosive environments.
3. The information and recommendations given herein are believed to be correct at time of writing. The data has been obtained from tests done under laboratory, or other controlled conditions and it is the users responsibility to use the data given in light of conditions on site, taking account of the intended use of the products concerned.
4. Whilst Gripple Ltd can give general guidance and advice, the nature of Gripple products means that the ultimate responsibility for selecting the correct product for a particular application must lie with the customer.
5. All products must be used, handled and applied in accordance with current product instructions and manufacturers recommendations for use, published by Gripple Ltd.

### Features / Benefits

- Supplied with Drop-in Anchors
- Available in M6, M8 and M10, up to 225 kg SWL, with a 5:1 safety factor
- Supplied as a ready-to-use kit with wire and Gripple hanger
- Available in lengths from 1 to 10m
- Other lengths are available on request
- Also available in Stainless Steel

### Specification

Size	Stud Diam	Tread Length (mm)	Overall Length (mm)
No.1 (0 - 15 kg)	M6	20	48
No.2 (15 - 45 kg)	M6	20	48
	M8	45	70
	M10	45	77
No.3 (45 - 90 kg)	M6	20	48
	M8	45	70
	M10	45	77
No.4 (90 - 225 kg)	M10	45	77

**Remark:** This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

### Solutions, Service and Supplies to the Trade

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ

T 01322 274226 F 01322 278178 E sales@fixmart.co.uk [www.fixmart.co.uk](http://www.fixmart.co.uk)

