



Product Model

Concrete Screw

Tapcon CSK Head

Fast installation – Cuts its own thread

Versatile: Slotted washered hex head version and Phillips flat head version available

Available in 5mm & 6mm and in lengths from 32 - 125mm, to cover a wide number of applications

Replaces small diameter expansion anchors, plugs and screws in light to medium duty applications

No need to pre-spot holes, no inserts required
Removable and adjustable and can be installed close to edges

Technical data
supplied by the
manufacturer



ITW CONSTRUCTION PRODUCTS

Code	Hole Diameter mm	Driver Bit	Fixture Thickness mm	Anchor Length mm	Min Hole Depth mm	Min Embedment mm
921507	4	PH2	0 – 7	32	35	25
921508	4	PH2	5 – 20	45	35	25
921514	5	PH3	5 -20	45	35	25
921515	5	PH3	17 – 32	57	35	25
921516	5	PH3	30 - 45	70	35	25

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

Solutions, Service and Supplies to the Trade

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ

T 01322 274226 F 01322 278178 E sales@fixmart.co.uk www.fixmart.co.uk

