

- ✓ RIGHT PRODUCTS
- ✓ RIGHT PLACE
- ✓ RIGHT TIME

Insulated (Lagged) Flexible Ductwork



Insulated (Lagged) Flexible Ductwork are thermally insulated with a glass wool layer in order to provide insulation such as when passing through unheated areas to minimise heat loss. As well as preventing heat loss the thermic insulation is suitable for preventing condensation and minimising loss of cold. Insulated (Lagged) flexible ductwork also offers some measure of acoustic attenuation.

Specification

Inner Duct	Perforated
Jacket	Aluminium/Polyester Fibreglass Yarn
Insulation 16kg/m ³	Fibreglass 25mm
Diameter Range (mm)	100-450
Temperature Range (°C)	-30 /+140
Maximum Air Velocity	30 m/sec
Maximum Positive Working Pressure	2000 Pa
Standard Length	10 metre

Technical data supplied by the manufacturer.

- Available sizes: 100mm up to 450mm.
- Tested for fire resistance and conforms to BS476 Parts 6, 7 & 20
- No special tools required for cutting or fixing
- In the event of a fire no toxic gases are emitted

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.