

- ✓ RIGHT PRODUCTS
- ✓ RIGHT PLACE
- ✓ RIGHT TIME



Universal Duct Clamp

Universal Duct Clamps can be used for coupling all types of rectangular flange systems, with no pre-clamping and drilling required.

Description

| | |
|-----------------------|---------------------------------|
| Supplied with: | M8 x 20 Set Screw |
| To Suit: | All Flange Systems and Profiles |

Technical Information

| | | |
|----------------------------|---|---|
| Material: | Galvanised Steel | Technical data supplied by the manufacturer |
| Steel Thickness: | 2.5mm | |
| Torque: | 5 N | |
| Gasket Compression: | 30 – 50% | |
| Fire Resistance: | Tested in accordance to UNE EN 1366-9:2009 “Fire resistance tests for service installations. Part 9: Single compartment smoke extraction ducts” and EN 1363-1:2020: “Fire resistance tests. Part 1: General Requirements”. LGAI Technological Center, S.A. (APPLUS), Barcelona. | |
| | Test report file number: 21/32306163-2 issued 01.03.2022 | |

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way. Any illustrations shown are indicative only, and dimensions may differ slightly from batch to batch.