



Product Model Universal Duct Clamp (Mez Clamp)

Universal Duct Clamp for the intermediate clamping of Slide-On Ductwork Flange Systems. It can be used in conjunction with all Rectangular Flange Systems.

Technical Information

Universal Flange Clamp formed of 3mm Zinc-Coated Steel, supplied with M8x25 8.8 grade bolt.

Product Guarantee

All component parts of the G Clamp are guaranteed against defective material.

Packaging Information

Box Quantity	200
Weight Per Box	8.67kg

Technical data
supplied by the
manufacturer



Installation Instructions

- 1 Prior to the fitting of 'G' Clamps, the Flanges should be pulled together with vice grips.
- 2 Sufficient pressure should be applied to compress the Gasket to ensure an airtight joint.
- 3 Start fitting the 'G' Clamps measuring from the corner bolt and work towards the centre of the duct at specified centres.

Low Pressure Ductwork	600mm centres
Medium Pressure Ductwork	450mm centres
High Pressure Ductwork	300mm centres

Note: The above information is given in good faith and for guidance only. All data is based upon average values. The purchaser shall be responsible for determining the suitability of this product for his purposes.

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.