

- ✓ RIGHT PRODUCTS
- ✓ RIGHT PLACE
- ✓ RIGHT TIME



Spiral Duct Clamp With M8/M10 Boss

Spiral Duct Clamps can be used for fastening spiral duct systems. The clamps include a noise insulating rubber lining which is formed around the steel band to prevent it sliding off when the spiral duct is slid through the clamp.

The clamps offer quick and convenient installation as a result of wide opening angles.

Technical data supplied by the manufacturer.

Description

Material: Galvanised Steel with Insulation Rubber

Dimensions: Width: 20mm Thickness: 1,8mm

Nominal Widths Available: 100mm to 400mm

Locking Screw: M6 x 20mm

Properties

- 2-part screw fixed pipe clamp with a welded on combination nut M8/M10.
- Sound insulation enclosure inserted in a positive lock.
- EPDM quality for DIN 4109.
- Insulation rubber, silicone and halogen free.
- Temperature resistant -30 °C to +70/80 °C.
- Quick and practice- oriented installation as a result of further opening angles.
- Easy installation as a result of a click-in lock $\varnothing \leq 400$ mm.
- Matches pipe tolerances as a result of 2 locking screws.
- Maximum load per pipe clamp: app. 70 kg.

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.