



## Silver Foil Tape

Aluminium Acrylic Foil Tape is generally used within heating and ventilation, such as for sealing foil faced insulation materials.

### TECHNICAL INFORMATION

**501104010** - 50mm x 45M, 30 Micron Thickness

**501104011** - 75mm x 45M, 30 Micron Thickness

**501104009** - 100mm x 45M, 30 Micron Thickness

Property	Unit	Value	Test Method
Total Thickness (without liner)	µm	65	PSTC-33 / ASTM D3652
Peel Adhesion (180°)	N/25mm	>16	PSTC-1 / ASTM D3330
Tack Rolling Ball	cm	< 10	PSTC-6 / ASTM D3121
Tensile Strength	N/25mm	> 45	PSTC-31 / SSTM D3759
Elongation	%	> 3.0	PSTC-31 / SSTM D3759
Application Temperature	°C	10 ~ 40	-
Heat Resistance	°C	-20 ~ 120	-

- ✓ It is essential, as with all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil.
- ✓ Should be stored at room temperature and kept from wet and heat source.
- ✓ Shelf life: One year from shipment date when stored at 21°C (70°F)/ 50% RH out of direct sunlight.
- ✓ Tolerance: Weight and Thickness: + 10%; Width: + 3mm; Length: Cut Roll: + 0.3m

