

- ✓ RIGHT PRODUCTS
- ✓ RIGHT PLACE
- ✓ RIGHT TIME



Blue Duct Cover Sticky Protection Film

Duct Cover Sticky Protection Film is a single sided self-adhesive polyethylene film, which is adapted to the specific requirements of HVAC systems.

It is weather-resistant, UV-resistant and can be removed quickly and without residue.

Available in blue-transparent rolls both 500mm and 1,000mm wide and 100m long.

Technical data supplied by the manufacturer.

Description

Dimensions: 500mm and 1,000mm Wide

Lengths: 100m Roll

Material: LDPE

Colour: Blue Transparent

Thickness: 0.04 - 0.05 mm

Weatherproof and UV-resistant: max. 3 months

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

- ✓ RIGHT PRODUCTS
- ✓ RIGHT PLACE
- ✓ RIGHT TIME

Benefits

- The tear-resistant film protects ductwork against dust and contamination during storage and transportation.
- Good adhesion properties on galvanised steel sheets and stainless steel and is suitable for sealing duct components.
- Film can be quickly removed without leaving any residue.

Technical Information

- Tear proof, single-sided self-adhesive polyethylene film for sealing air ducts, pipes, formed parts and other ducting components in accordance with VDI 6022.
- Breaking load (N/25mm): 28
- Elongation of break (%): 230
- Adhesive: Polyacrylate dispersions
- Breaking load (N/25mm): 3.5
- Processing temperature range (temperature of object and ambient temperature): +15°C - 45°C
- Lift off temperature for the removal of the film (surface area temperature and ambient temperature): >+5°C
- Use a laminating device with rubberised pressurised rollers
- Avoid stretching the film and forming bubbles/creases when laminating
- The rolls of film can be stored for 6 months. They should be protected from dust and moisture
- The film is not suitable for heavy duty deep drawing.

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

MEP & HVAC FIXING SPECIALISTS

Springhead Enterprise Park, Springhead Road, Northfleet, Kent DA11 8HJ
 T 01322 274226 F 01322 278178 E sales@fixmart.co.uk www.fixmart.co.uk