

- ✓ RIGHT PRODUCTS
- ✓ RIGHT PLACE
- ✓ RIGHT TIME



## Rubber Foot with Strut

Rubber Foot with Strut is a rubber foot with 41 x 21mm aluminium strut pre-inserted for quick and easy installation.

The foot can be used to support pipework, runs of cable tray, condenser units and other equipment.

### Description

Dimensions Available: L x W x H

250 x 180 x 95mm

400 x 180 x 95mm

600 x 180 x 95mm

1000 x 180 x 95mm

Specification: 41 x 21mm Aluminium Pre-Inserted

Size	Max Loading Per Foot (kg)
250 mm	160
400 mm	240
600 mm	450
1000 mm	645

Technical data supplied by the manufacturer.

### Benefits

- ✓ Made from durable recycled rubber they are environmentally friendly
- ✓ Suitable for internal or external applications in temperatures between -40C to + 80C. BSEN60068-2-14

### Material Specification

SBR-Recycled Rubber. Bound using a ratio of high-quality moisture curing Polyurethane Pre-Polymer.

BS7188:1989+A2;2009 and EN1176-7:2008

**Remark:** This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way. Any illustrations shown are indicative only, and dimensions may differ slightly from batch to batch.