

- ✓ RIGHT PRODUCTS
- ✓ RIGHT PLACE
- ✓ RIGHT TIME



Cold Galvanising Paint

Cold Galvanising Paint (500ml aerosol) provides fast drying rust protection for use on light rust or clean metal. The product is suitable for touch-up of new, bare steel or galvanised steel in light industrial exposures, corrosive environments and high humidity areas.

Technical Information

Basis of binder	Epoxy-Ester
Colour	Grey
Coverage	1.5 - 2m ²
Temperature Resistance	Up to 350°C
Storage Stability	10 years if appropriate storage provided - 10°-25°C, humidity max. 60%
Size	500ml Aerosol
VOC Content	634g/lit
Drying Times @ 20°C Touch Dry	10 – 15 Minutes

Technical data supplied by the manufacturer

Features and Benefits

- ✓ 90% Pure Zinc content in dry film
- ✓ 1000 hours salt spray resistance
- ✓ Temperature Resistant to 350°C

Environmental and Disposal Information

- ✓ This product has been supplied 100% free of heavy metals.
- ✓ Caps and Packaging are made of recyclable material.
- ✓ Emptied cans should be placed in recycling skips or appropriate containers. Cans which are not empty should be disposed of as special refuse.

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way. Any illustrations shown are indicative only, and dimensions may differ slightly from batch to batch.