

- ✓ RIGHT PRODUCTS
- ✓ RIGHT PLACE
- ✓ RIGHT TIME

FSC® Certified Foil-Faced Hardwood Blocks



Load bearing rings for pipe installation / management. These hardwood blocks are from a sustainable wood source which has been certified by the Forest Stewardship Council® (FSC®).

Wood blocks made from at least FSC Mix 70% certified timber under Chain of Custody Code: **FSC® C153138**



The mark of
responsible forestry

Description

Tree Species: Triplochiton scleroxylon K. Schum.

Material Source: Tropical West Africa

Technical Information

Temperature Limit (C°): 100 Max

Density (Kg³): 380

Pipe Dimensions (mm): 15-356

Block Thickness (mm): 15, 20, 25, 30, 35, 40, 50

Block Length (mm): 95

Note blocks can also be cut to required sizes.

Foil: A 30-Micron class 'o' aluminium foil. With a service temperature of -30°C ~ +120°C

Remark: This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way. Any illustrations shown are indicative only, and dimensions may differ slightly from batch to batch.