



## Product Model Zamac Nail In Anchors

- Variety of uses including: Fixing of brick ties, conduit clips, signs and drywall track into concrete and masonry
- Fast and easy installation

### Materials

- Concrete
- Stone

### Technical Data

Substrate	Concrete ≥ 25 N/mm <sup>2</sup>
Size Ø (mm)	6
Drill Hole Ø (mm)	6
Embedment Depth (mm)	25
Min Drill Hole Depth (mm)	35
<b>Rec. Tensile Load (kN) Nrec</b>	<b>0.70</b>
<b>Rec. Shear Load (kN) Vrec</b>	<b>1.22</b>

Not recommended for overhead applications such as suspended ceilings.

### Zamac Nail In Anchors

Part Code	Size Ø x Length (mm)	Max Fixture Thickness (mm)	Fixture Clearance Hole (mm)	Box Qty	Carton Qty	Pallet Qty
0630ZNA	6 x 30	5	6.5	100	1,800	64,800
0640ZNA	6 x 40	15	6.5	100	1,000	30,000
0650ZNA	6 x 50	25	6.5	100	800	24,000
0665ZNA	6 x 65	40	6.5	100	800	24,000

**Remark:** This technical data sheet replaces all previous versions. The technical data contained herein is given in good faith and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings. The information detailed in this technical data sheet is given by way of indication and is not exhaustive, users should contact either the seller or the manufacturer of the product for additional technical information concerning its use, if they think the information in their possession needs to be clarified in any way.

Technical data supplied by the manufacturer



### Key Features

- Steel nail
- Large diameter flange head to firmly secure attachments
- Zinc alloy body

### Installation Guide

- Drill a hole to the required diameter and depth
- Position the fixing through the attachment and into the substrate.
- Hammer nail into anchor to secure